



## SPECIFICATION FOR PREFABRICATED LIGHT BUILDING External and Internal Walls 6 cm PRESS PANEL (Fibercement +EPS+ Fibercement)

**INTRODUCTION:** Prefabricated light buildings can be applied to all kinds of layout plan required in such a way that their widths and lengths will be multiples of 125 cm depending on their intended use. Panel used measures 1250mm by 2500 mm. Prefabricated light buildings are designed so as to be capable of more than one assembling and disassembling. All architectural planning, design and technical drawings are carried out with ARCHICAD 9 TR, STRUCAD (Structural Steel Detailing System Versiyon-16), STA4CAD, ÇELİKPROIV and AutoCAD programs, and engineering calculations are performed with SAP 2000 and CFS programs by our technical personnel. All materials used have TSE certification.

<b>TECHNICAL DATA</b>	Snow load	<b>80 kg/m<sup>2</sup></b> (Varies according to snow region characteristic and altitude at the installation place) <b>TS 498 and TS EN 1991-1-3</b>
	Wind speed	<b>102 km/hour (50 Kg/ m<sup>2</sup>) TS 498 and TS EN 1991-1-4</b>
	External wall thermal conductivity	<b>K: 0,62 Kcal/m<sup>2</sup> hC (K: 0,72 W/m<sup>2</sup> K)</b>
	Internal wall thermal conductivity	<b>K: 0,59 Kcal/m<sup>2</sup> hC (K: 0,68 W/m<sup>2</sup> K)</b>
	Roof thermal conductivity	<b>K: 0,39 Kcal/m<sup>2</sup> hC (K: 0,45 W/m<sup>2</sup> K)</b>
	Earthquake zone	Effective ground acceleration coefficient: <b>A<sub>0</sub>=0,40</b> (1.degree earthquake zone)
		Structural importance coefficient ( <b>I =1</b> )
		Live load participation factor ( <b>n = 0,3</b> )
		<b>According to intended use and type of building I =1 / 1,2 / 1,4 / 1,5 ,</b> Calculated as <b>n = 0,3 / 0,6</b>
	APPLICABLE STANDARDS	<b>DESIGN &amp; STRUCTURAL :</b> TS EN 1993-1-1 , 1-2, 1-8+AC, (EUROCODE 3) , TS 11372, TS 498 ,TS 648,TS 6793, TS EN 1991-1-1-3 , 1-1-4 (EUROCODE 1), TS EN 1998-1 (EUROCODE 8) , IMO-01.R-01/2005, Specification for Buildings to be Built in Seismic Zones – 2007
		<b>Material:</b> DX51D+Z (~St 37) no. 1311, S250GD+Z no. 1325, S320GD+Z grade no.1332 , S350GD+Z (~St 52) grade No 1335, standard DIN EN 10346-00, structural steel galvanized by zinc coating.
		<b>Production;</b> Galvanized cold-formed trusses, purlins and H-section steel profile columns manufactured in the roll forming line
		<b>Fasteners:</b> Two panels are joined by fitting them into H-section steel columns, and such H profile is joined with roof trusses using zinc-plated bolts & nuts. DIN 960-961, DIN 935-F,8.8
		<b>Thermal Insulation :</b> Thermal insulation requirements for buildings (8.05.2000)
		<b>Acoustic insulation :</b> TS 187 and TS 854 (DIN 4109)
<b>Fire resistance :</b> DIN 4102 Fire classification of construction products and building elements - 2002		
Climate zone		Wall insulation is suitable for 1st climate zone (K:0,80 W/m <sup>2</sup> K).

### Genel Müdürlük

E-5 Karayolu Üzeri Yanyol No: 18  
Güzelyalı - Pendik / İstanbul / Türkiye  
Tel: +90 216 392 2128  
Fax: +90 216 392 93 08

### İzmir Şube

Ankara Caddesi No: 281  
Bornova / İzmir / Türkiye  
Tel: +90 232 374 14 22  
Fax: +90 232 374 11 46

### Adapazarı Hendek Şube

Kargalıhanbaba Mahallesi Sakarya Cad.  
No: 336/A Hendek / Adapazarı / Türkiye  
Tel: +90 264 654 58 30-31  
Fax: +90 264 654 58 29

### Giresun Şube

Atatürk Bulvarı Teyyaredüzü Mahallesi  
No: 355 Giresun / Türkiye  
Tel: +90 454 215 55 55  
Fax: +90 454 215 00 87



		Roof insulation is suitable for ~ 2 <sup>nd</sup> climate zone (K:0,40 W/m <sup>2</sup> K).
<b>FOUNDATION</b>	Concrete will be applied in accordance with the concrete layout plan (foundation dimensions) delivered by <b>ÖZGE YAPI A.Ş.</b> Foundation design, structural calculations and covering of foundation and floor will be carried out by the <b>EMPLOYER</b> . Building will be anchored to the foundation floor with steel anchor bolts and dowels. Reinforced spread foundation or mesh-reinforced foundation must be prepared over compacted soil.	
<b>EXTERNAL AND INTERNAL WALLS</b>	Exterior panel height	<b>2500 mm</b>
	External wall dimensions/ thickness	<b>1250x2500x60 mm</b>
	Surfaces	<b>8 mm Fibercement (Hekimboard/Boardia) flat board - Class A1 (Fireproof)</b>
	Insulation	<b>44 mm thick polystyrene foam ( EPS ) - , fire class B1</b>
<b>CEILING COVERING</b>	Entire space	<b>6 mm Fibercement (Hekimboard/Boardia) board - EN 13051-1 Class A1 (Fireproof) or painted plaster board"</b>
	Insulation	<b>80 mm glass wool blanket</b>
<b>ROOF</b>	Covering	<b>0,45 mm thick unpainted galvanized sheet steel with 27 x 200 mm pitch depth. <u>Black sponge is used under eaves and ridge for isolation.</u></b>
	Purlin	<b>Angle omega-section (80x50x0,9 mm) profile cold formed from galvanized rolled sheet steel in the roll forming line</b>
	Truss	Located at an interval of <b>125 cm</b> , steel truss designed specially with exterior and interior profiles and manufactured from high standard galvanized rolled sheet steel (thickness of sheet steel changes between 0,8-2 mm according to structural calculations and construction requirements) 150x300 mm PVC louver on the face of exterior trusses for ventilation.
	Eaves	20 cm PVC eaves. <b>150x150 mm PVC louver at eaves to avoid bleeding.</b>
	Gutter and downspouts	Metal gutter and PVC downspouts are included. (Breakage that may be resulting from snow is excluded from the scope)
	<b>LOAD-BEARING SYSTEM</b>	Composed of <b>H-section columns manufactured from (galvanized sheet steel)</b> and roof trusses from <b>high standard galvanized roll sheet steel</b> in the roll forming line. It is also possible to use by modifying wall thickness and width of profiles or with industrial profiles and DKP/Galvanized column-beam reinforcement and welding/screw/bolt as a result of structural calculations, when required.
<b>WALL JOINTS</b>	<b>Galvanized sheet steel H-profiles</b> manufactured in the roll forming line are bolted to trusses and frames.	
	One face of H profiles at the juncture of external walls are covered with PVC sheath ( <b>in order to prevent bleeding</b> )	
<b>CEILING JOINTS</b>	6 mm Fibercement (Hekimboard/Boardia) ceiling material is joined using such joining elements as galvanized sheet steel and PVC omega profile, PVC sheath and painted aluminum T-profile.	
<b>ACCESSORIES</b>	Edge omega, omega over panel, face edge coating material, face coating material, window rough bucks, coating material located under the eaves are made of PVC (in order to avoid corrosion and bleeding).	
	NOTE: Edge omega, omega over panel, window rough bucks, and face sheet can be metal according to building construction.	
<b>DOOR JOINERY</b>	<b>Exterior door:</b>	<b>845/1960 mm Insulated sheet steel door (external dimensions)</b>
	1,2 mm galvanized bare sheet steel frame	(Both sides with chipboard, EPS filler inside 0,500 mm thick prepainted RAL9002 galvanized sheet steel) leaf thickness: <b>45 mm</b>
	<b>Interior door:</b>	<b>External dimensions 840/1960 mm American panel door, (wooden carcass, kraft filler ) leaf thickness :42 mm</b>
	<b>Wet area door</b>	External dimensions <b>720/1960 mm American panel door</b> , (wooden carcass, kraft filler) leaf thickness: <b>42 mm</b>

#### Genel Müdürlük

E-5 Karayolu Üzeri Yanyol No: 18  
Güzelyalı - Pendik / İstanbul / Türkiye  
Tel: +90 216 392 2128  
Fax: +90 216 392 93 08

#### İzmir Şube

Ankara Caddesi No: 281  
Bornova / İzmir / Türkiye  
Tel: +90 232 374 14 22  
Fax: +90 232 374 11 46

#### Adapazarı Hendek Şube

Kargalıhanbaba Mahallesi Sakarya Cad.  
No: 336/A Hendek / Adapazarı / Türkiye  
Tel: +90 264 654 58 30-31  
Fax: +90 264 654 58 29

#### Giresun Şube

Atatürk Bulvarı Teyyaredüzü Mahallesi  
No: 355 Giresun / Türkiye  
Tel: +90 454 215 55 55  
Fax: +90 454 215 00 87



	<b>Door lock and handle</b>	Exterior and interior door locks are cylindrical (interior doorlocks of housing are mortise locks), door handles are brass or grey metal.		
<b>WINDOW JOINERY</b>	Window (PVC frame)	<b>1205/1000 mm</b>		
	Transom window (PVC frame)	<b>1205 / 500 mm</b>		
<b>GLASS</b>	Double glazed	<b>4+9+4 mm –</b>		
<b>PAINT</b>	Exterior surfaces	2 layers of Silicone based housepaint-		
	Interior surfaces and ceiling	2 layers of plastic based indoor paint-		
	Other	No primer is required for galvanized cold formed truss, purlin and H profile since weldless technology is used. Note: Paint color should be notified one week before the shipment at the latest by the customer. Otherwise, standard paint colors will be delivered.		
	Non-galvanized metal components	1 layer Rapid primer+ exterior surfaces 2 layers of oil paint -		
<b>ELECTRIC WIRING Surface mounted</b>	Cable	(NYM ,220 Volt , 50 Hz.),		
		PVC cable conduit (16 mmx25 mm ) water-resistant cable inside,		
		Socket outlets 3X2.5 mm <sup>2</sup> NYM, socket lines 4X2.5 mm <sup>2</sup> NYM cable		
		Lighting fixtures 2X1.5 mm <sup>2</sup> NYM, lines 3X1,5 mm <sup>2</sup> NYM cable ,		
	Lighting fixtures	Normal area	Circular fluorescent (for housing) , 2*36 W -1*36 W- 2*18 W -1*18 W- Fluorescent TMS Fixture, Fluorescent lamps	
		Wet area	Glop –IP 44,	
		Above exterior door		
	Sockets, switches	Damp places		
	Fuse, fuse boxes	Automatic fuses		
		PVC Fuse boxes		
Power panel, Weak current installations (Telephone, TV, data), Mainline connections:	<b>Will be provided by the Employer company.</b>			
<b>SANITARY PIPING Surface mounted</b>	Sanitary wares/mixers	Wash basins	<b>40x50 cm wall hung type</b>	
		Wash basin and shower taps	Taps are mounted on the wall in cold water installed wash basins, and taps are mounted to the wash basin in hot water installed wash basins.	
		Toilet	Toilet with plastic cistern (European WC) Squat toilet (bidet nozzles)	
		Shower tray	80 cmx80 cm Acrylic	
		Kitchen sink	<b>50/100 cm</b> sink is made from chrome material, double cabinet from melamine coated chipboard at the bottom. Upper cabinet is not available.100 cm kitchen sink cabinet.	
	Pipes	Fresh water	PPRC -	
		Sewage water	PVC -	
<b>OTHER</b>	<b>Foundation floor must be prepared according to the concrete layout plan provided by Özge Yapı A.Ş. EMPLOYER company shall assume the full responsibility in case it fails to observe the explanations in the concrete layout plan provided by Özge Yapı A.Ş.</b>			

**ÖZGE YAPI SAN ve TİC. AŞ. RESERVES ITS RIGHT TO MAKE CHANGES IN ALL TECHNICAL DETAILS THEREOF.**

**Genel Müdürlük**

E-5 Karayolu Üzeri Yanyol No: 18  
Güzelyalı - Pendik / İstanbul / Türkiye  
Tel: +90 216 392 2128  
Fax: +90 216 392 93 08

**İzmir Şube**

Ankara Caddesi No: 281  
Bornova / İzmir / Türkiye  
Tel: +90 232 374 14 22  
Fax: +90 232 374 11 46

**Adapazarı Hendek Şube**

Kargalıhanbaba Mahallesi Sakarya Cad.  
No: 336/A Hendek / Adapazarı / Türkiye  
Tel: +90 264 654 58 30-31  
Fax: +90 264 654 58 29

**Giresun Şube**

Atatürk Bulvarı Teyyaredüzü Mahallesi  
No: 355 Giresun / Türkiye  
Tel: +90 454 215 55 55  
Fax: +90 454 215 00 87

**Genel Müdürlük**

E-5 Karayolu Üzeri Yanyol No: 18  
Güzelyalı - Pendik / İstanbul / Türkiye  
Tel: +90 216 392 2128  
Fax: +90 216 392 93 08

**İzmir Şube**

Ankara Caddesi No: 281  
Bornova / İzmir / Türkiye  
Tel: +90 232 374 14 22  
Fax: +90 232 374 11 46

**Adapazarı Hendek Şube**

Kargalıhanbaba Mahallesi Sakarya Cad.  
No: 336/A Hendek / Adapazarı / Türkiye  
Tel: +90 264 654 58 30-31  
Fax: +90 264 654 58 29

**Giresun Şube**

Atatürk Bulvarı Teyyaredüzü Mahallesi  
No: 355 Giresun / Türkiye  
Tel: +90 454 215 55 55  
Fax: +90 454 215 00 87